CASSETTE AWNING / RESIDENTIAL FACADE



TECHNICAL SUMMARY / 03

CASSETTE AWNINGS

A cleaner facade when the shade is not in use.

LCF and LCG cassette systems conceal the fabric and folding arms in one enclosure, combining a controlled visual line with exterior sun control.

WIDTH

Up to approx. 7 m

PROJECTION

Up to approx. 4 m

MOUNTING

Wall / ceiling detail

REFERENCE SUMMARY Indicative configurations. Confirm against current production data.

CASSETTE AWNINGS

Large openings require coordinated design decisions.

INDICATIVE SPECIFICATION

MODEL FAMILIES	LCF / LCG, subject to current production range
WIDTH	Approx. 2.5-7.0 m in documented standard combinations
PROJECTION	Approx. 1.5-4.0 m in documented standard combinations
OPERATION	Manual, electric, or remote control
CONTROLS	Wind / sun sensor options where specified
STRUCTURE	Aluminium cassette with folding-arm mechanism

PROJECT QUESTIONS

01 Is the closed line important?

02 Is there depth for the cassette?

03 Is the fixing substrate adequate?

04 What projection is needed?

05 Where will power and service access be?

06 How will the awning be operated in wind?

SPECIFICATION NOTE

A sensor can automate retraction but does not make an awning storm-proof. Safe operating limits and user behavior remain part of the specification.

REQUEST A SAMPLE OR QUOTATION

sales@yajumeng.com

https://www.yajumeng.com